



A Component Casting Resin Slow 6325

Safety Data Sheet

pursuant to Regulation (EC) No 453/2010

Publication date: 03/08/2021

Revision date: // Version: 1.0

SECTION 1: Identification of the substance or mixture and of the company/undertaking				
1.1	Product identification Product form: Mixture Product code: Dutch Resin Group Component A, 6325 Product group: Casting resins			
1,2	Relevant identified use Main use category Industrial/ Professional use spec. Use of the substance or the mixture Forms of use that are advised against	:	Use, Hobby Decoupage/ jewelry Parental supervision is required for use by minors. No additional information available	
1.3	Dutch Resin Group Gladsaxe 19 7327 JZ Apeldoorn T +31 (0)55 312 44 65 info@dutchresin.nl			
1.4	Emergency number: T +31 (0)55 312 44 65 This number is only available during office hours.			
	Land	Official advisory body	Address	Emergency number
	NETHERLANDS	National Poisons Information Center. University Medical Center Utrecht, The National Poisons Information Center (NVIC) informs doctors, veterinarians, pharmacists, and other healthcare professionals about the possible health effects and treatment options for poisonings. The NVIC is available for this purpose day and night, both by telephone and via the internet.	P.O. Box 85500 3508 GA Utrecht	+31 30 274 88 88
SECTION 2: Identification of hazards				
2.1	Classification of the substance or mixture			
	Classification in accordance with Regulation (EC) No 1272/2008 [CLP] Skin Irrit. 2 H315 Eye Irrit. 2 H319 Skin Sens. 1 H317 Aquatic Chronic 2 H411 Full text of the H-phrases: see section 16 Adverse physicochemical, health and environmental effects: No additional information available			
2.2	Adverse physico-chemical, health and environmental effects			
	No additional information available Labelling in accordance with Regulation (EC) No 1272/2008 [CLP] Classification in accordance with Regulation (EC) No 1272/2008 [CLP] Unclassified Hazard Pictograms (CLP):			
				

A Component Casting Resin Slow 6325

Safety Data Sheet

pursuant to Regulation (EC) No 453/2010

Publication date: 03/08/2021

Revision date: // Version: 1.0

	GHS07 GHS09
	Signal word (CLP): Warning
	Hazardous components: reaction product: bisphenol-A-epichlorohydrin, epoxy resin (mean molecular weight \dot{y} 700), bisphenol-f type epoxy resin, oxirane, mono[(C12-14-alkoxy)methyl]-derivatives
	Hazard statements (CLP): H315 - Causes skin irritation H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H411 - Toxic to aquatic organisms, with long-lasting effects
	Safety Recommendations (CLP): P261 - Avoid inhalation of vapor, gas, mist, smoke, spray, dust P273 - Avoid release into the environment P280 - wear protective gloves, protective clothing P302+P352 - IF IN CONTACT WITH SKIN: Wash with plenty of water P305+P351+P338 - IF IN CONTACT WITH EYES: rinse carefully with water for several minutes; remove contact lenses, if possible; continue rinsing
	P501 - Dispose of contents/packaging to a collection point for hazardous or special waste, in accordance with local, regional, national and/or international regulations

2.3	Other dangers
	No additional information available

SECTION 3: Composition and information on ingredients

3.1	Dust																				
	Not applicable																				
3.2	Mixture of hazardous and non-hazardous substances																				
	<table border="1"> <thead> <tr> <th>name</th> <th>Product identification</th> <th>%</th> <th>Classification in accordance with Regulation (EC) No 1272/2008 [CLP]</th> </tr> </thead> <tbody> <tr> <td>reaction product: bisphenol-A-epichlorohydrin, epoxy resin (mean molecular weight \dot{y} 700)</td> <td>(CAS No.) 25068-38-6 (EC No) 500-033-5 (EU-Identification number) 603-074-00-8</td> <td>70-90 Eye</td> <td>Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411</td> </tr> <tr> <td>oxirane, mono[(C12-14-alkoxy)methyl]-derivatives</td> <td>(CAS No.) 68609-97-2 (EC No) 271-846-8 (EU-Identification number) 603-103-00-4</td> <td>5-15 Skin</td> <td>Irrit. 2, H315 Skin Sens. 1, H317</td> </tr> <tr> <td>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate</td> <td>(CAS No.) 41556-26-7 (EC No.) 255-437-1</td> <td>1-<10</td> <td>H303 H317 H411</td> </tr> <tr> <td>Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate</td> <td>(CAS No.) 82919-37-7 (EC No.) 280-060-4</td> <td>1-<10</td> <td>H303 H317 H361 H411</td> </tr> </tbody> </table>	name	Product identification	%	Classification in accordance with Regulation (EC) No 1272/2008 [CLP]	reaction product: bisphenol-A-epichlorohydrin, epoxy resin (mean molecular weight \dot{y} 700)	(CAS No.) 25068-38-6 (EC No) 500-033-5 (EU-Identification number) 603-074-00-8	70-90 Eye	Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	oxirane, mono[(C12-14-alkoxy)methyl]-derivatives	(CAS No.) 68609-97-2 (EC No) 271-846-8 (EU-Identification number) 603-103-00-4	5-15 Skin	Irrit. 2, H315 Skin Sens. 1, H317	Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	(CAS No.) 41556-26-7 (EC No.) 255-437-1	1-<10	H303 H317 H411	Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	(CAS No.) 82919-37-7 (EC No.) 280-060-4	1-<10	H303 H317 H361 H411
name	Product identification	%	Classification in accordance with Regulation (EC) No 1272/2008 [CLP]																		
reaction product: bisphenol-A-epichlorohydrin, epoxy resin (mean molecular weight \dot{y} 700)	(CAS No.) 25068-38-6 (EC No) 500-033-5 (EU-Identification number) 603-074-00-8	70-90 Eye	Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411																		
oxirane, mono[(C12-14-alkoxy)methyl]-derivatives	(CAS No.) 68609-97-2 (EC No) 271-846-8 (EU-Identification number) 603-103-00-4	5-15 Skin	Irrit. 2, H315 Skin Sens. 1, H317																		
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	(CAS No.) 41556-26-7 (EC No.) 255-437-1	1-<10	H303 H317 H411																		
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	(CAS No.) 82919-37-7 (EC No.) 280-060-4	1-<10	H303 H317 H361 H411																		
	Full content of the R, H and EUH phrases: see section 16																				

SECTION 4: First aid measures

A Component Casting Resin Slow 6325

Safety Data Sheet

pursuant to Regulation (EC) No 453/2010

Publication date: 03/08/2021

Revision date: // Version: 1.0

4.1	Description of the first aid measures
	<p>General First Aid: Never administer anything by mouth to an unconscious person. If feeling unwell, consult a doctor (show them this label if possible).</p> <p>First aid after inhalation: Allow to breathe fresh air. Let the victim rest.</p> <p>First aid after contact with skin: Remove contaminated clothing, wash the skin with copious amounts of water or shower (for 15 minutes), and consult a doctor if necessary.</p> <p>First aid after contact with eyes: Rinse immediately and thoroughly with water. Seek medical help if pain or redness persists.</p> <p>First aid after ingestion: Rinse the mouth. DO NOT induce vomiting. Consult a doctor urgently.</p>
4.2	Symptoms/injuries
	<p>after inhalation: May cause an allergic skin reaction. after contact with skin: Causes skin irritation.</p>
4.3	Indication of the required immediate medical care and special treatment
	No additional information available
SECTION 5: Firefighting measures	
5.1	Extinguishing equipment
	<p>Suitable extinguishing agents: Foam. AFFF. Water mist.</p> <p>Unsuitable extinguishing agents: Do not use a strong water jet. Dry powder.</p>
5.2	Special hazards caused by the substance or mixture
	No additional information available
5.3	Advice for firefighters
	<p>Fire precautions: No open flames, no sparks, and no smoking.</p> <p>Extinguishing instructions: Do not enter the fire zone without suitable safety equipment, including respiratory protection. Protection during firefighting: Cool the exposed vessels with a water spray or mist. Other information: Exercise extreme caution when fighting a chemical fire.</p>
SECTION 6: Measures in the event of accidental release of the substance or mixture	
6.1	Personal precautions, protective equipment and emergency procedures
	General measures: No smoking
6.11 For	persons other than emergency services
	<p>Protective equipment: Equip cleaning staff with appropriate protection. Emergency procedures: Keep spectators at a distance.</p>
6.12 For	the emergency services
	No additional information available
6.2	Environmental precautions
	<p>Clean up the spilled product as quickly as possible using an absorbent product. Do not allow to flow into the sewer system or public waters.</p>
6.3	Methods and material for containment and cleaning up For containment :
	Use suitable waste containers. Cleaning methods: Clean up spilled product as soon as possible using an absorbent product.
6.4	Reference to other sections
	Regarding waste disposal after cleaning, see section 13. See section 8 for

A Component Casting Resin Slow 6325

Safety Data Sheet

pursuant to Regulation (EC) No 453/2010

Publication date: 03/08/2021

Revision date: // Version: 1.0

		regarding the use of personal protective equipment.
SECTION 7: Handling and storage		
7.1	Precautions for the safe handling of the substance or mixture	
		Wash hands and other exposed parts with mild soap and water before eating, drinking, smoking, or leaving work. Ensure good ventilation in the processing area to avoid the formation of fumes.
7.2	Conditions for safe storage,	
		Including incompatible products. Storage conditions: Store only in the original packaging in a cool, well-ventilated place. Keep the containers closed when not in use. Incompatible substances: Strong alkalis. Strong acids. Remove all sources of ignition. Protect the product from direct sunlight.
7.3	Specific end-use	
		A Component floor system
SECTION 8: Exposure control measures/personal protection		
8.1	Control parameters	
		No additional information available
8.2	Measures to control exposure	
		Personal protective equipment: Avoid unnecessary exposure. Gloves. Safety glasses. Hand protection: Wear protective gloves. Eye protection: Safety glasses. Respiratory protection: Wear a suitable mask. Other information: Do not eat, drink, or smoke during use.
SECTION 9: Physical and chemical properties		
9.1	Information about basic physical and chemical properties	
		Physical state: Liquid Color: transparent Odor: characteristic. Odor threshold : No data available pH : No data available Relative evaporation rate (butyl acetate=1) : No data available Melting point : No data available Freezing point : No data available Boiling point : No data available Flash point : No data available Autoignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) : Non-flammable Vapor pressure : No data available Relative vapor density at 20 °C : No data available Relative density : No data available Solubility : No data available Log Pow : No data available Kinematic viscosity : No data available Dynamic viscosity : No data available Explosive properties : No data available Oxidizing properties : No data available Explosion limits : No data available

A Component Casting Resin Slow 6325

Safety Data Sheet

pursuant to Regulation (EC) No 453/2010

Publication date: 03/08/2021

Revision date: // Version: 1.0

9.2	Other information
	No additional information available
SECTION 10: Stability and reactivity	
10.1	Reactivity
	No additional information available
10.2	Chemical stability
	Not determined.
10.3	Possible dangerous reactions
	Not determined
10.4	Conditions to be avoided
	Extremely high or low temperatures. Protect from direct sunlight.
10.5	Chemically interacting materials
	strong acids. Strong alkalis
10.6	Dangerous decomposition products smoke.
	Carbon monoxide. Carbon dioxide.
SECTION 11: Toxicological information	
11.1	Information about toxicological effects
	<p>Acute toxicity : Not classified</p> <p>Skin corrosion/irritation : Causes skin irritation.</p> <p>Serious eye damage/eye irritation : Causes serious eye irritation.</p> <p>Respiratory/skin sensitization: May cause an allergic skin reaction.</p> <p>Germ cell mutagenicity: Not classified. Classification criteria are not met based on available data. Carcinogenicity: Not classified. Classification criteria are not met based on available data. Reproductive toxicity: Not classified. Classification criteria are not met based on available data. Specific target organ toxicity (single exposure): Not classified. Classification criteria are not met based on available data. Specific target organ toxicity (repeated exposure)</p> <p>Not classified Based on the available data, the classification criteria are not met</p> <p>Inhalation hazard : Not classified Based on the available data, the classification criteria are not met</p> <p>Potential harmful effects on human health and possible symptoms Based on the available data, the classification criteria are not met.</p> <p>Specific target organ toxicity - Single exposure no data available</p> <p>Specific target organ toxicity - Repeated exposure no data available</p> <p>Aspiration hazard: no data available</p>
SECTION 12: Ecological information	
	<p>Ecotoxicology Assessment</p> <p>Acute aquatic toxicity: no data available</p> <p>Chronic aquatic toxicity: no data available</p>

A Component Casting Resin Slow 6325

Safety Data Sheet

pursuant to Regulation (EC) No 453/2010

Publication date: 03/08/2021

Revision date: // Version: 1.0

12.1	Ecology - water
	Toxic to aquatic organisms, with long-lasting effects.
12.2	Persistence and degradability
	Can cause long-term harmful effects in the environment
12.3	Bioaccumulation:
	no data available
12.4	Mobility in the soil
	No additional information available
12.5	Results of PBT and zPzB assessment
	No additional information available
12.6	Other harmful effects
	Avoid discharge into the vicinity.
SECTION 13 Disposal instructions	
13.1	Waste processing methods
	Recommendations for waste disposal: Dispose of safely in accordance with local/national regulations. Prevent discharge into the environment
SECTION 14: Information regarding transport	
	Land transport (ADR / RID / GGVSEB)
14.1	UN number:
	ADR-UN Number: 3082 IATA-UN Number: 3082 IMDG-UN Number: 3082
14.2	Proper shipping name in accordance with the UN Model Regulations:
	ADR Shipping Name: ENVIRONMENTALLY HAZARDOUS LIQUID, NEG Description on transport document UN 3082 ENVIRONMENTALLY HAZARDOUS LIQUID, NEG (CONTAINS ; reaction product: bisphenol-A-epichlorohydrin, epoxy resin (mean molecular weight \geq 700)(25068-38-6) CONTAINS ; bisphenol-f type epoxy IATA Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, NOS IMDG Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, NOS
14.3	Transport hazard class(es): 9
	ADR Class: 9 ADR - Hazard identification number: 90 IATA Class: 9 IATA Label: 9 IMDG-Class: 9 IMDG Class: 9
14.4	Packaging group:
	ADR Packing Group: II IATA Packing group: II

A Component Casting Resin Slow 6325

Safety Data Sheet

pursuant to Regulation (EC) No 453/2010

Publication date: 03/08/2021

Revision date: // Version: 1.0

		IMDG-Packing group: II
14.5	Environmental hazards:	
		Environmental risks (Marine pollutant): -
14.6	Special precautions for the user:	
		Yes, keep separate from food items, luxury food items, food items
14.61	Land Transport Classification Code (ADR):	
		M6 Special provision (ADR): 274, 335, 601 Limited quantities (ADR): 5l Excepted quantities (ADR): E1 Packing instructions (ADR): P001, IBC03, LP01, R001 Special packing requirements (ADR): PP1 Special requirements for joint packing (ADR): MP19 Instructions for transport tanks and bulk containers (ADR): T4 Special provisions for transport tanks and bulk containers (ADR): TP1, TP29 Tank code (ADR): LGBV Tank transport vehicle: AT Transport category (ADR): 3 Special provisions for transport - Parcels (ADR): V12 Special provisions for transport - Loading, unloading and handling (ADR): CV13 Hazard number (Kemler no.): 90 Orange identification mark: 90/ 3082 Tunnel restriction code (ADR): E
14.62	Transport on the open sea	
		Special provision (IMDG): 274, 335 Limited quantities (IMDG): 5 L Excluded quantities (IMDG): E1 Packing instructions (IMDG): P001, LP01 Special packing requirements (IMDG): PP1 IBC packing instructions (IMDG): IBC03 Tank instructions (IMDG): T4 Special provisions for tanks (IMDG): TP2, TP29 No. NS (Fire): FA No. NS (Waste) : SF Stowage Category (IMDG) : A
14.63	Air Transport PCA	
		Expected quantities (IATA): E1 PCA Limited quantities (IATA): Y964 PCA limited quantity max. net quantity (IATA): 30kg PCA packing regulations (IATA): 964 PCA max. net quantity (IATA): 450L CAO packing regulation (IATA): 964 CAO max. net quantity (IATA): 450L Special provision (IATA): A97, A158 ERG code (IATA): 9L
14.64	Transport on inland waterways	
		Classification code (ADN): M6 Special provision (ADN): 274, 335, 61 Limited quantities (RDN): 5 L Exceptional quantities (ADN): E1 Transport permitted (ADN): T Required equipment (ADN): PP Number of blue cones/lights (ADN) : 0 Not covered by the ADN: No

A Component Casting Resin Slow 6325

Safety Data Sheet

pursuant to Regulation (EC) No 453/2010

Publication date: 03/08/2021

Revision date: // Version: 1.0

	<p>Eye Irrit. 2 Serious eye damage/eye irritation, Category 2 Skin Irrit. 2 Skin corrosion/irritation, Category 2 Skin Sens. 1 Skin sensitization, Categories 1 H315 Causes skin irritation H317 May cause an allergic skin reaction H319 Causes serious eye irritation H411 Toxic to aquatic organisms, with long-lasting effects</p>
	<p>Other information: # REACH Declaration: All information is based on current knowledge. Consistency of the data in this Safety Data Sheet with the data stated in the Chemical Safety Report has been considered to the extent that these were available at the time of compilation (see Version number and Revision date).</p> <p>DISCLAIMER OF LIABILITY The information in this sheet was obtained from sources that are, to the best of our knowledge, reliable. However, the information was provided without any guarantee—directly implied—as to its accuracy. The conditions or methods of handling, storage, use, or finishing of the product are beyond our control and influence and may also be beyond our knowledge. For these and other reasons, we accept no liability whatsoever, while liability for losses, damage, or expenses that may arise in any way from the handling, storage, use, or finishing and disposal of the product is expressly disclaimed.</p>