

9025 Facade Seal THIX

Dutch Resin Group BV
 Gladsaxe 19
 7327JZ
 Apeldoorn
 Netherlands
 Tel: +31 55 312 44 65
 Email: sales@dutchresin.nl
 Web: www.dutchresin.nl

Product description

This 9025 Gevelseal THIX is a specially developed facade cream for facing bricks and offers long-lasting protection against moisture, driving rain, and pollution. Due to its water-repellent properties, it prevents moisture penetration while remaining vapor-permeable. Ideal for maintaining a clean and durable facade, it reduces the risk of moss and algae growth.

Product details

Packaging size	Set size
5 Liters	5 Liter Tin
10 Liters	10 Liter Can

Appearance Transparent

Shelf life 12 months after the production date when stored at normal temperature (15 °C). See more under *storage*

Product features

- Water-repellent and breathable.
- Increases resistance to frost and de-icing salt damage.
- UV-resistant for long-lasting protection.
- Easy and precise to apply without material waste.
- Strong beading effect

Areas of application

- Suitable for the impregnation of mineral substrates.
- Protects facades against driving rain. Reduces pollution and prevents moss growth.
- Ideal for porous, mineral building materials outdoors.
- Provides extra protection against driving rain with curative cavity and interior insulation.

Technical specifications

Similar mass (density)	0.83 kg/d m ³
Mixing ratio	N/A
Consumption	100 to max 250 g/m ² per layer.
Processing time	N/A
Dust dry	After 4 hours *
recoatable	After 8 hours *
Fully loadable	3 days
Viscosity (mPa.S)	3000 – 6000
Active ingredient content	25%

At normal temperature of 20°C.

Product processing conditions

Subsurface temperature	Minimum 5°C, maximum 30°C, Optimal 20°C
Ambient temperature	Minimum 5°C, maximum 30°C, Optimal 20°C
Subsurface moisture content	Moisture < 4%
Relative humidity	Maximum 70% RH
Dew point	at least 3°C above the dew point.
Pay attention	These conditions apply to both the processing and evaporation of the product. Apply the product only to clean and dry surfaces.
Tools	The product must be applied with a block brush or thick-haired roller to distribute it over the facing bricks.

Work and environmental protection

Storage and shelf life

Solvent-free. Non-flammable: Contains Polysiloxane, no hazards. Non-corrosive.

Wear suitable protective gloves and safety glasses during processing. Do not allow to enter open water or soil. Observe, among others, hazard/safety instructions on the can label and the safety data sheet. Odor-neutral after evaporation and ecologically and physiologically harmless.

Removal of material

Product residues that have not hardened. Do not allow to enter sewers, open water, or soil. These unevaporated components are chemical waste. Evaporated components are classified as construction waste.

The product must be stored dry at temperatures of at least 10 and at most 25 degrees. Under these conditions, the shelf life of an unopened package is at least 12 months. Store the packaging in a frost-free place.

Cleaning

The cleaning